

Digital Multimeter



FEATURES :

- * 8 Functions AC/DC Voltage, AC/DC Current, Resistance Capacitance, Diode Test and Audible Continuity Beeper
- * High Voltage 1000V and 20A Current Range
- * 0.5% Basic DCV Accuracy
- * LCD Display

GDM-8034 (3 1/2 Digits)

SPECIFICATIONS

DC VOLTAGE	Range Accuracy Input Impedance	200mV, 2V, 20V, 200V, 1000V 5ranges. ±(0.5% rdg + 1 digit) 10MW
AC VOLTAGE	Range Accuracy Input Impedance	200mV, 2V, 20V, 200V, 750V 5ranges. 40Hz ~ 500Hz±(1% rdg + 4 digits) 10MW
DC CURRENT	Range Accuracy	200μA, 2mA, 20mA, 200mA, 2A, 20A 6 ranges 200μA ~ 200mA±(0.5% rdg + 1 digit) 2A ~ 20A±(1% rdg + 3 digits)
AC CURRENT	Range Accuracy	200μA, 2mA, 20mA, 200mA, 2A, 20A 6 ranges 40Hz ~ 500Hz on all ranges, 200μA ~ 200mA±(1% rdg + 4 digits) 2A ~ 20A±(1.5% rdg + 2 digits)
RESISTANCE	Range Accuracy	200W, 2k, 20k, 200kW, 2MW, 20MW 6 ranges. 200W ~ 2MW±(0.75% rdg + 1 digit), 20MW±(1.5% rdg + 5 digits)
CAPACITANCE	Range Accuracy Test Freq.	2nF, 20nF, 200nF, 2μF, 20μF 5 ranges ±(2% rdg + 4 digits) 300Hz±5%
DIODE TEST	Test Current Open Voltage	Max. 2.5mA Max. 3.2V
CONTINUITY BEEPER	Description Test Current Open Voltage	Buzzer sounds if conductance less than 30W Max. 2.5 mA Max. 3.2V
DISPLAY		0.5" LCD display
POWER SOURCE		AC 110V/220V± 15%, 50/60Hz
ACCESSORIES		Power cord x 1, Instruction manual x 1, Test lead GTL-107A x 1
DIMENSIONS & WEIGHT		245(W) x 95(H) x 280(D) mm, Approx. 2kg

E5

ISO-9001 & ISO-14001